



Roof Tape

SUPERIOR SEALING TAPE

- ✓ Thin tape, does not tear
- ✓ Very good adhesion
- ✓ Water and windproof

Technical Info

- Support: laminated aluminium film reinforced with P.E.
- Adhesive mass: modified butyl rubber.
- Thickness: 0,7 mm.
- Specific weight: 1050 gr/m².
- Resistance:
 - temperature: -30°C to +100 °C.
 - water: excellent.
 - U.V.: very good.
 - solvent: not resistant.
- Shelf life: cool and dry: 1 year.

Packing

Roof Tape - roll 10m * 50mm	603058000
Roof Tape - roll 10m * 100mm	603258000
Roof Tape - roll 10m * 150mm	603158000

Product

Characteristics

- A cold-bonding aluminium sealing tape for general use.
- Consists of a laminated aluminium support, composed of 2 thin layers of aluminium with between them a polyethylene film, and a tack coat of modified butyl rubber, covered with a protective film.
- Advantages:
 - very high tear resistance
 - very flexible and easy to apply
 - very high initial tack to most building materials
 - overpaintable
 - UV-resistant

Applications

- Ideal for lead repairs.
- Sealing verandas.
- Adheres perfectly to concrete, stone facing, lead, zinc, steel, aluminium, lacquer work, roofing and glass.
- Sealing of drain pipes.

Use

- Application temperature between +5°C and +40°C. .
- Apply to a clean, dry and stable surface.
- Cut off to the desired length and remove protective film.
- Apply without leaving air bubbles and press down firmly.